



## DHL Desktop Printer

Discover how powerful a simple and compact desktop printer can be.

The DHL desktop printer is ultra-light, compact for best space utilization and support multiple communication ports. They are effective and multitasking for printing retail, warehouses, logistic & transportation, health care labels and tags.



# Specification



## Desktop Printer

Model		RJ45/USB/Seriell	Dongle (WIFI / BT)	USB/Seriell (Standard)
<b>PrintMethod</b>		Direct Thermal		
<b>Resolution</b>		203 dpi (8 dots/mm)		
<b>PrintSpeed</b>		7 IPS (177 mm/s)	,36 PPV	
<b>PrintWidth</b>		4.25" (108 mm)		
<b>PrintLength</b>		Min. 0.16" (4 mm); Max. 68" (1727 mm)		
<b>3URFHVVR</b>		U32Bit RISC CPU		
<b>Memory</b>	<b>Flash</b>	8 MB (4 MB for user storage)		
	<b>SDRAM</b>	16 MB		
<b>SensorType</b>		Adjustable reflective sensor.Fixed transmissivesensor,central aligned		
<b>Media</b>	<b>Types</b>	Continuous form,gap labels, black mark sensing,and punched hole; label length set by auto sensing or programming		
	<b>Width</b>	Min. 1" (25.4 mm). -Max.4.64" (118 mm)		
	<b>Thickness</b>	Min. 0.003" (0.076mm) - Max. 0.008" (0.203 mm)		
	<b>Label Roll Diameter</b>	Max. 5" (127 mm)		
	<b>Core Diameter</b>	1" (25.4 mm), 1.5" (38.1mm)		
<b>PrinterLanguage</b>		EZPL, GEPL, GZPL, GDPL, auto switch		
<b>Software</b>	<b>Label Design Software</b>	GoLabel (for EZPL only)		
	<b>Driver</b>	Vista, Windows 7, Windows 8 & 8.1, Windows 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, MAC, Linux		
	<b>SDK</b>	Win CE, .NET, Andriod, Windows Vista, Windows, Windows 8 & 8.1, Windows 10, Mac, iOS		
<b>Resident Fonts</b>	<b>Bitmap Fonts</b>	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions		
	<b>TTF fonts</b>	TTF fonts (Bold / Italic / Underline ). 0°, 90°, 180°, 270° rotatable		
<b>Download Fonts</b>	<b>Bitmap Fonts</b>	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable		
	<b>Asian Fonts</b>	16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese (G B2312), Japanese (S-JIS), Korean (KS-X1001) 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions		
	<b>TTF fonts</b>	TTF fonts (Bold / Italic / Underline ). 0°, 90°, 180°, 270° rotatable		
<b>Barcodes</b>	<b>1-D Bar codes</b>	China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8, EAN-13, EAN 8/13 (with 2 & 5 digit extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (12 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT- 128, ITF14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Random Weight, Standard 2 of 5, Telepen, UPC-A, UPC-E, UPC-A and UPC-E with EAN 2 or 5 digit extension, UCC 128, UCC/EAN-128 K-Mart		
	<b>2-D Bar codes</b>	Aztec code, Code 49, Codablock F, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39, GS1 Composite		
<b>Code Pages</b>		CODEPAGE E 437, 737, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode UTF8 UTF16BE UTF16LE		
<b>Graphics</b>		Resident graphic filetypes are BMP and PCX, other graphic formats are downloadable from the software		
<b>Interfaces</b>	USB 2.0 (B-Type)		Dongle Version (WIFI or BT)	USB Device (B-Type)
	Serial port: RS-232 (DB-9)			
	IEEE 802.3 10 / 100 Base-Tx Ethernet port (RJ-45)			
<b>Control Panel</b>		Function Key: FEED / One Tri-color LED: Power (Green, Orange and Red)		
<b>Power</b>		Auto Switching 100-240VAC, 50-60Hz.		
<b>Environment</b>	<b>Operation Temperature</b>	41°F to 104°F (5°C to 40°C)		
	<b>Storage Temperature</b>	-4°F to 122°F (-20°C to 50°C)		
<b>Humidity</b>	<b>Operation</b>	30-85%, non-condensing.		
	<b>Storage</b>	10-90%, non-condensing.		
<b>Agency Approval</b>		CE (EMC) J FCC Class A J CB ° F8 / ° (\$ & ° . & ° & &		
<b>Dimension</b>	<b>Length</b>	8.58" (218 mm)		
	<b>Height</b>	6.53" (166 mm)		
	<b>Width</b>	6.61" (168 mm)		
<b>Weight</b>		3.17 lbs (1.44 Kg) , excluding consumables		
<b>Options &amp; Accessories</b>		Cutter module Label Dispenser External label roll holder for 250mm External label rewinder		