





Affordable Performance Excellence

Despite its budget-friendlytag, ME30K boasts latest OS Android 13,MediaTek octa-core processor, ample 4GB RAM +64GB eMMC storage, and a high-capacity battery of 4800 mAh.

Versatile Wireless Reach

With WLAN, WPAN, WWAN, and dual nano SIM, ME30K ensures seamless connectivity. Experience optimal signal strength and easy pairings.

Robust & Reliable Build

ME30K's 5 ft./ 1.5mdrop rating and IP67 protection ensure resilience against water, dust, and impacts. Built for prolonged performance.

Advanced Scanning & Decoding

Built-in Honeywell HS7 module guarantees rapid scans, even for damaged barcodes. Equipped with 5MP front and 13MP rear cameras.













Android 13

MediaTek CPU

4800mAh

IP67

WiFi & 4G LTE

4.0"(480x800)



Main Features



Operating System

Android 13 Upgradeable to Android 14



Processor

MediaTek MT6765Octa-core, 2.0GHz



Memory

RAM: 4GB, ROM: 64GB



Dimensions(L×W×H)

159.4 x 64.6 x 15.0 mm 6.28 in. x 2.54 in. x 0.59 in.



Weight

231g/8.15oz.(With battery) 151.8g/5.36oz.(Without battery)



Display

4.0 in.IPS, 480x800



Touch Panel

Panda Glass
Multi-modecapacitive touch,
wet hand operation and glove operation,
the screen sinks to prevent the
screen from falling and breaking.



Power

3.85V,4800mAh



SIM

Standard: nano SIM x2



Audio

1.5WSpeaker Single mic USB Type-Cport



Buttons

Enterprise physical alphanumeric keypad (26 physical buttons)



Sensor

Acceleration sensor, proximity sensor, light sensor



NFC

ISO14443 Type A and B; Mifare/FelliCa and ISO15693 cards; Reader mode, P2P mode and Card Emulation



Scan Engine

Standard: HS7 Option: SE5070



Camera

Front: 5MP Rear: 13MP, autofocus, flash and 1080p video shooting



PAN

Bluetooth BT5.0+BR/EDR+BLE



LAN

2.4G/5G dual frequency
IEEE 802.11a/b/g/n/acWave 1802.11r,
OKC,PMKID caching,IPv4, IPv6



WAN

GSM: B2/B3/B5/B8; WCDMA: B1/B2/B5/B8; TD-SCDMA: B34/B39 FDD-LTE: B1/B2/B3/B5/B7/B8/B20/B28a&b TDD-LTE: B34/B38/B39/B40/B41



GPS

GPS, A-GPS Beidou, GLONASS, Galileo



Environment

Operating Temp.: -20°C to 55°C Storage Temp.: -40°C to 70°C Humidity: Temperature $55^{\circ}\text{C} \pm 2^{\circ}\text{C}/131^{\circ}\text{F} \pm 35.6^{\circ}\text{F}$, relative humidity $90^{\circ}\text{RH} \pm 3^{\circ}\text{C}^{\circ}\text{RH}$



Sealing

P67

1.5mdrop to concrete over



Accessories

Standard: Power adapter/Type-CUSB Cable/HandStrap Option: Single slot cradle/Holster/Protective Boot

